

5200 LED





○ WH / White

Series of recess office lighting, comprising:


- Direct & indirect light fitting provides uniform and extra soft lighting distribution
- Easy replacement of the LED module in just a few simple steps
- Save up to 60% energy comparing to T5 fluorescent lamps
- Housing and secondary reflector made of white painted sheet steel
- High transmittance metal perforated diffuser with frosted laid in or opal polycarbonate diffuser
- Color tolerance according to MacAdam 3 SDCM
- CRI 90, 3000K/3500K/4000K options
- Built-in LED driver, non dim/0-10V/DALI options
- Nano coating option
- Custom made size upon request



Two Taikoo Place



Options



Perforated metal diffuser



Frosted PC diffuser




CIC GREEN
PRODUCT CERTIFICATION
CICGPC-L-24003(LED)



Zhaga comply LED product

5200 LED PERFORATED METAL DIFFUSER							IP20
CODE	WATTAGE (W)	KELVIN	CRI	OPTIC BEAMS	LIGHTSOURCE LUMEN OUTPUT (lm)	DIMENSION L(mm)	LIFETIME
LED 220-240V 50/60Hz							
5200-LED-12	12.7	4000	90	100°	2411	595	50,000h
5200-LED-24	25.4	4000	90	100°	4822	1195	50,000h
5200-LED-48	38.1	4000	90	100°	7233	1495	50,000h



LED 25.4W

5200 LED OPAL PC DIFFUSER							IP20
CODE	WATTAGE (W)	KELVIN	CRI	OPTIC BEAMS	LIGHTSOURCE LUMEN OUTPUT (lm)	DIMENSION L(mm)	LIFETIME
LED 220-240V 50/60Hz							
5200-LED-18	12.7	4000	90	100°	2411	595	50,000h
5200-LED-36	25.4	4000	90	100°	4822	1195	50,000h
5200-LED-54	38.1	4000	90	100°	7233	1495	50,000h



Six Pacific Place, Admiralty