

AQUATEC FINE URETHANE

Water Borne Polyurethane Finish Coat

Description	: Modification of Water-base Polyurethane paints
Type	: Polyurethane Resin
Color	: Wide range of colors as per color card. Special colors on request
Finish	: Matt / Semi Matt
Uses	: For the interior and exterior application of walls, ceilings, and other cement - rendered surfaces. Applicable for new substrates and repainting.
Features	: <ul style="list-style-type: none">● Excellent durability. It can be used as topcoat of spray tile and elastic coatings as well as flat finish● Low odor and easy and safe to handle because it is water based● Excellent weathering resistance, gloss retention and water resistance same as solvent borne polyurethane paint● No pot life because it is one pack

APPLICATION DATA

Method	: Brush, roller & spray
Theoretical Coverage	: Theoretical — 0.15~0.16kg/ m ² Practical — Depends on substrate condition, application method etc.
Dilution	: Max. 5 ~ 10% use clean water Brush — 0.15kg/m ² Roller — 0.15kg/m ² Spray — 0.16kg/m ²
Surface Preparation	: Surface should be completely dry. (water content below 19% by protimeter, pH value below 10). Avoid painting when the temperature is below 5°C or the humidity is over 85%.
Drying Time	: Touch dry — 10 min. Dust Free 30 min Overcoat Time — ≥2 hrs. *Above values are standard. The actual data may vary slightly depending on the application conditions, methods and surface conditions.
Cleaning	: All equipment should be cleaned with water as soon as possible after use while paint is still soluble.

Recommended : Sealer – 1 coat of Ultra Sealer III or approved water based sealer by Nippon
Painting System Paint
Topcoat – 2 coats of Aquatec Fine Urethane

GENERAL INFORMATION

Solid Content : 52±4% by volume

Specific Gravity : 1.25 (at 20°C)

Packing : 20kg

Storage : Microbial contaminants cause paint to spoil. Keep excess paint clean, reseal lid and store in cool and dry place.

Shelf Life : 36 months in sealed original packaging stored at room temperature and shaded place.

Note : The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific applications, please contact Nippon Paint Sales & Marketing Department. We reserve the right to modify our product specification without further notice.

For further enquiries, please call:

Sales & Marketing Department

NIPPON PAINT (H.K.) CO., LTD.

Tel : (852) 2699 9333

Fax : (852) 2602 8844

Http : www.nipponpaint.com.hk