

LED T5 HE ECG



Features

- Energy saving with low power consumption
- Good color rendition, Ra ≥ 80
- Smooth operation even at low temperatures
- No mercury and hazardous substances
- Beam Angle: 270°
- Full glass body


LED	HE
8W	~ 14W
12W	~ 21W
16W	~ 28W
20W	~ 35W



- No Re-wiring*
- Broad compatibility with ballasts

EU - TUBE


G5 base



Model	Wattage	Color Temp	Beam Angle	Type	Length L1 / L2	Efficacy	Lumen	ENERGY LABEL
LED F8T5/E/830/600	8W	3000K	270°	14W HE ECG	549mm / 563mm	110lm/W	880lm	A+
LED F8T5/E/840/600	8W	4000K	270°	14W HE ECG	549mm / 563mm	115lm/W	920lm	A+
LED F8T5/E/865/600	8W	6500K	270°	14W HE ECG	549mm / 563mm	120lm/W	960lm	A+
LED F12T5/E/830/900	12W	3000K	270°	21W HE ECG	849mm / 863mm	110lm/W	1320lm	A+
LED F12T5/E/840/900	12W	4000K	270°	21W HE ECG	849mm / 863mm	115lm/W	1380lm	A+
LED F12T5/E/865/900	12W	6500K	270°	21W HE ECG	849mm / 863mm	120lm/W	1440lm	A+
LED F16T5/E/830/1200	16W	3000K	270°	28W HE ECG	1149mm / 1163mm	110lm/W	1760lm	A+
LED F16T5/E/840/1200	16W	4000K	270°	28W HE ECG	1149mm / 1163mm	115lm/W	1840lm	A+
LED F16T5/E/865/1200	16W	6500K	270°	28W HE ECG	1149mm / 1163mm	120lm/W	1920lm	A+
LED F20T5/E/830/1500	20W	3000K	270°	35W HE ECG	1449mm / 1463mm	110lm/W	2200lm	A+
LED F20T5/E/840/1500	20W	4000K	270°	35W HE ECG	1449mm / 1463mm	115lm/W	2300lm	A+
LED F20T5/E/865/1500	20W	6500K	270°	35W HE ECG	1449mm / 1463mm	120lm/W	2400lm	A+

Actual performance may vary depending on ballast output

Direct retrofit in T5 HE ECG circuit*



- Suitable for direct retrofit to 1x, 2x HE electronic ballast
- Compatible with T5 Fluorescent Emergency Kit
- Compatibility with 3x, 4x T5 fluo. HE electronic ballast depending on brand / model

* Comply to EN62776