

Camel Excellent Interior Emulsion Anti-Mould & Virus 252 series

PRODUCT INTRODUCTION

Recommended Uses	Suitable for interior ceilings and plastered cementitious walls.
Description	Camel Excellent Interior Emulsion Anti-Mould & Virus 252 series is specially formulated with anti-viral and anti-bacterial performance. It is proven to be effective against virus H1N1 and Staphylococcus aureus, efficacy is over 99.9%. This product is also anti-bacterial and mould proof.
Features	<ul style="list-style-type: none"> ● Anti-viral and anti-bacterial ● 5 years mould proof warranty mould proof ● Low odour and environmental friendly ● Good hiding
5 Years Mould Warranty	<ul style="list-style-type: none"> ● Register your product to put warranty coverage in force on Camel.com.hk/warranty. ● By using our online warranty registration, you will be able to enjoy 5 year of Mould Free Warranty service for your Camel Excellent Interior Emulsion Anti-Mould & Virus 252 series. ● Warranties are available for Hong Kong & Macau consumers only. ● Please read and understand the service policy clearly before you register for your product. ● If product information incorrect, Yip's Camel (HK) Ltd. reserves the right to change or cancel service.
Standard Packing	1L & 4L

TECHNICAL DATA

Base Resin	Acrylic copolymer
Color	Standard colors or personalized color by computerized tinting machine
Finish	Matt
Calculated Coverage	Around 12m ² /ltr. @30 microns dry film thickness per coat Actual coverage depends on surface conditions and also application conditions.
Drying Time (@ 25°C)	<ul style="list-style-type: none"> ● Touch Dry --- 1 hour ● Hard Dry --- 2 hours ● Overcoating --- Minimum 2 hours

APPLICATION

Recommended Primer	Camel Alkali Resistant Wall Sealer MA473
Recommended Thinner	Clear Water
Method of Application	<ul style="list-style-type: none"> ● Ready-to-use after thinning with clear water and stirring thoroughly ● Thinning Ratio Brush / Roller --- Dilute 10 parts of the paint with around 1 to 4 parts of clear water (10 : ~ 1 to 4 by volume). ● Recommended no. of coats : 2 coats

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Camel

Excellent Interior Emulsion Anti-Mould & Virus

252 series

APPLICATION	
Surface Preparation	<ul style="list-style-type: none"> ● For new wall <ul style="list-style-type: none"> --- The substrate should be cured at least 30 days. The alkalinity (pH) of the surface should be < 10 before painting and water content of the substrate should be < 15%. --- Fill up cracks and depression to get a smooth surface with appropriate filler. --- Ensure the surfaces to be coated are sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. ● For recoated surface <ul style="list-style-type: none"> --- All chalked and scaled materials must be removed before painting. --- Apply patching paste to get a smooth surface before painting. --- Apply AquaPro Super Anti-Mould Wash 111 (dilute 2 parts of Super Anti-Mould Wash 111 with 1 part of clear water) on mould affected area, and stay more than 6 hours. --- After 6 hours, clean with new towel and water. --- Use new towels in each process, to avoid cross contamination. --- Ensure the surfaces to be coated are sound, clean, free from dust, rust, oil, grease, moisture and foreign matters.
Clean Up After Application	Clean up all the application equipment with water while Camel Excellent Interior Emulsion Anti-Mould & Virus 252 series is still wet.
SAFETY PRECAUTION	
Dangerous Goods Classification	Not applicable.
Shelf-Life	36 Months.
Application Conditions	<ul style="list-style-type: none"> ● Maintain temperature in areas to receive coatings at minimum 8 deg. C, during application and until coatings have cured. ● Avoid applying the product when relative humidity above 85%. ● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. ● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. ● Post "Wet Coating" signs while work is in progress and while coatings are curing.
Product Storage, Delivery & Handling	<ul style="list-style-type: none"> --- Material to be delivered and stored in undamaged, original manufacturers' containers. --- Keep container closed when not in use. --- Store at cool, dry place. Store above freezing point.
Health & Safety Precautions	<ul style="list-style-type: none"> ● Ingestion --- Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. ● Eye contact --- Flush immediately with water and get medical care. ● Skin contact --- Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention. ● Inhalation --- Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Flat Coatings P09-02
VOC content (ready to use)	Not exceeding 50gm/litre

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.