SPECIFICATION



SUPPLIER



Company Name	Leigei Stone Company Limited				
Address	Room 1107, Startex Industrial Building, 14 Tai Yau Street,				
	Snapokong, Hong Kong				
Contact person	Rex Yau	Mobile no.	+852 98532282		
Email	rexyau@leigeistone.com/ rexyauhk@gmail.com				

PRODUCTS

Item	Reconstituted Stone for Wall Finish					
Manufacturer	Yunfu Leigei Stone Company Limited					
	www.leigeistone.com					
Materials	Leigei Reconstituted Stone is the excellent product of premium					
	minerals and recycled materials more advanced and sustainable					
	on the market, manufactured with the exclusive and innovative					
	technology.					
	Various sizes, grains and color tones of the most precious stones					
	are skillfully blended with quality resins to obtain superior,					
	versatile and technically advanced beautiful surfaces.					
	Leissi Deservit tod Stars sives a sentema yru internatation of					
	Leigei Reconstituted Stone gives a contemporary interpretation of					
	the timeless look of stone, available in different color nuances and					
	particle sizes, expertly blended to give a touch of sophistication to					
	any environment.					
	Our products offer a large choice of colors, textures and exclusive finishes. Nuances, composition and sizes can be fully customized.					
	Waterjet cutting and fabrication are also available for further					
	personalization					
Composition	Leigei Reconstituted Stone is over 90% recycled and eco-friendly					
	natural minerals and 5-7% of high-quality resins.					
Thickness	Standard thickness includes 12mm, 15mm, 18mm, 20mm, 25mm,					
	30mm. Other thickness is also available on demand.					

Color	Light beige white					
Finish	Polished / Honed / Matt					
Slab	3000mm x 1200mm, 3000mm x 1400mm, 3200mm x 1600mm					
Dimension						
Quality	Leigei Reconstituted Stone is manufactured under the quality					
Assurance	management requirements of the ISO 9001 standard, the					
	environmental management requirements of the ISO 14001					
	standard					
Product						
specification	Characteristics	Standard	Unit	Value		
	Density	EN 14617-1	Kg/m ³	2366		
	Water absorption	EN 14617-1	%w/w	0.03		
	Flexural strength	EN 14617-2	mPa	65.2		
	Compressive strength	EN 14617-15	mPa	244		
	Abrasion resistance	EN 14617-4	mm	28.7		
	Linear thermal	EN 14617-11	°C ⁻¹	3.01 x 10 ⁻⁶		
	expansion coefficient					
	Dimensional stability	EN 14617-12	Class	А		
	Resistance to	EN 14617-10	Class	C4		
	chemicals (acids)					
	Reaction to fire	EN 13501-1		A2-fl-s1		
	Moh's hardness	EN 15771		6		
	Slip resistance	DIN 51130		Polish: R9		
				Honed: R12		
	The above data is indicative and non-binding. Actual test data can be					
	supplied on request.					
	eigei Reconstituted Stone contributes towards achieving					
	certifications such as LEED, BREEAM, WELL etc					