

Cair Interior Paint

Product Description:

Purifies airborne pollutants for healthier indoor air quality. Unlike traditional paints, cair is certified VOC-Free, releases zero odours and includes anti-molding, anti-bacterial and humidity regulating features.



Product Type:

Water-based
Interior Emulsion Paint

Colour:

Colour atlas
available upon request

Packaging:

1 Litre,
5 Litres, 20 Litres

Finish:

Matte

Product Features:

Certified VOC-Free (<2g/L)
Odourless
Purifies Airborne Pollutants
Anti-Bacterial
Anti-Molding
Absorbs & Desorbs Moisture
Easy Application

Design Use:

- 1. Best suited for interior wall and ceiling surfaces such as cement, plaster and fibreboard.
- 2. Suitable for common areas like void decks and corridors.
- 3. Can be used on other material surfaces that are properly primed.

Solid Content:

50 ± 2% by weight (based on white)

Specific Gravity:

1.45 ± 2% by kg/litre (based on white)

Storage:

Store in a tightly sealed container in a cool, dry place.

Shelf Life:

Up to 18 months in a tightly sealed container.

Application:

Method: Roller, brush, paint sprayer
Coverage: 10-12m² / litre (30 microns DFT)
Dilution: Not more than 10% dilution with water.
Cleaning Solvent: Clean water

Drying & Over-Coating Time:

Coating Interval (with recommend topcoat)
Touch Dry: 30 mins (at 25°C)
Minimum over-coating interval: 2 hours (at 25°C)

Surface Preparation:

- 1. Remove loose bonding film, dirt, peeling paint, etc by high-pressure water jet or mechanical methods (power brush, scraper), whichever is suitable.
- 2. Remove fungus, algae and biological contaminants: Wash affected areas, then apply anti-fungal solution and leave on for at least 2 hours.
- 3. Fill cracks with suitable exterior-grade water-resistant putty or filler.
- 4. Remove dust, foreign matter and powdery residue with damp cloth.
- 5. Ensure surface is clean, dry and stable:
 - No water residue on the substrate surface.
 - Surface moisture must be <5%

Precaution Instructions Before Use:

- 1. Use appropriate personal protective equipment throughout application.
- 2. Avoid direct contact with sensitive skin.
- 3. Ensure good ventilation during paint application and drying.
- 4. Keep out of reach of children.
- 5. Do not store near food or articles intended for consumption by humans or animals.
- 6. Keep containers tightly closed at all times.
- 7. Do not allow paint to enter drains and watercourses.
- 8. Do not reuse the paint container.

Declaration:

The information given intends to give a description of the products’ performance under specific test conditions. Nevertheless, we cannot assume any responsibility for differences during use, since circumstances under which the products are applied in practice are subjected to many variations. We reserve the right to alter the given data without notice.

For enquiries, contact:

6692 9000
hello@gowithgush.com
www.gowithgush.com