

INTERMATT PLUS PRO

Acrylic Emulsion Paint

PRODUCT DESCRIPTION

Water-based, low VOC (Volatile Organic Content) low odour environmental friendly coating incorporating special acrylic resin

USES

As a decorative and protective finishing coat for internal walls and ceilings

AREA OF APPLICATION

Suitable primed surfaces of interior concrete, plaster, masonry, gypsum boards, hard and soft boards, asbestos board, timber and metal surface, etc.

CHARACTERISTICS

- Low VOC (Volatile Organic Content) and low odour
- Excellent resistance against fungus and alkali
- Forms a flat and tough film when cured
- Superior adhesion and hiding power
- Dries quickly to a durable and decorative finish
- Washable

COLOUR AVAILABILITY

Wide range

TECHNICAL DATA

Finish	Matt	
Specific Gravity	1.45 ± 0.05 (depending on colour)	
Drying Time (At 30°C)	Surface Dry	30 minutes
	Hard Dry	1 hour
Shelf Life	Up to 12 months if stored in tightly sealed containers. Keep under roof and in cool place.	
Film Thickness	Dry Film (Theoretical)	40 – 60 microns
Solid Content	60 ± 3% ⇒ 60 ± 3%	
Viscosity	85 ± 10KU/30°C	

SURFACE PREPARATION

Surface shall be dry and free from dirt, dust, oil, grease and foreign matter. Surface unevenness, cracks etc shall be made good with our cementitious filler.

APPLICATION DATA

No. of Component	: One
No. of Coat	: Two
Coverage	: 0.15 – 0.20kg/m ² /coat
Dilution	: 0 – 15% by wt with water
Overcoating Interval	: 3 hours
Method of Application	: By Spray, Brush or Roller

PACKING STYLE

Intermatt Plus Pro	24kg/can
--------------------	----------

MATERIAL HANDLING

- * Store materials in a cool, well-ventilated and dry place, away from direct sunlight.
- * Ensure adequate ventilation during application.
- * Avoid contact with skin or eyes. Any skin or eye contamination should be washed immediately with plenty of water and seek medical treatment.
- * If swallowed, seek medical advice immediately. Do not induce vomiting.
- * Keep away from heat sources.
- * It is not advisable to use Internal grade emulsion paint to the common area where rain water may contact with the painted surface. (Eg: Corridor, Staircase etc)

METHOD OF CLEANING APPLICATION

Clean with clear water or mild detergent by wiping in case (before surface drying)

Note: The above technical information/ values are given to the best of our knowledge based on laboratories tests, and practical experience. However, due to different applications, site conditions and constraints which are beyond our control, we are not liable for any circumstances due to or relating to the application of usage of our products. We reserve the right to alter or modify any given data without prior notice; therefore it is best to contact us should you have any doubts or enquires.