

# Programmable Microwave Sensor LED T8 Tube


Series Type: PM



Flick Free  
(無閃爍)  
保護視力

## Features 產品特點 >>

- Microwave controlled internal sensor
- Sensor detection distance of 3-8 meter (user selectable)
- 0%-90% lumen in standby mode (user selectable)
- 5s-60mins Delay/exit time in standby mode
- SPM Design – power circuit protection to cut off individual LEDs when mal-functioned
- Compatible in use with most emergency battery brands
- 微波控制內部感應器 感應器探測距離3-8米(用戶可選擇)
- 0%-90%流明(用戶可選擇)
- 待機狀態下延時/退出時間5秒-60分鐘
- SPM設計-電源電路保護,在故障時切斷單個LED
- 與大多數應急電池品牌相容



## Specification 產品規格 >>

Model 型號	Voltage 電壓 (V)	Wattage 功率 (W)	Length 長度 (mm)	Lamp Life 光衰壽命 (Hrs)	Colour Temp 色溫 (K)	Lumen Output 輸出流明 (Lm/W)	Color Rendering 顯色度 (CRI)	Lamp Base 燈腳	PCS/CTN 每箱數量 (pcs)
LT-10609-PM128A	100-240	9	600	50000	3000/4000/6500	120	>80	T8_G13	25
LT-10912-PM128A	100-240	12	900	50000	3000/4000/6500	120	>80	T8_G13	25
LT-11218-PM128A	100-240	18	1200	50000	3000/4000/6500	120	>80	T8_G13	25
LT-11522-PM128A	100-240	22	1500	50000	3000/4000/6500	120	>80	T8_G13	25

- Light efficiency (lm/W)/Power (W), Color Rendering Index (CRI), Can be customized according to customer needs
- Our Standard Power factor (PF) > 0.9 and Total harmonic index THD < 15%, According to customer requirements can produce a lower THD < 10%
- This type of certification is issued by a government-approved laboratory for Safety certification, Fire testing, Restriction of Hazardous Substances (RoHS), Photobiological safety of lamps and lamp systems, (an Exemption Group) and other test certifications to ensure product quality
- 光效 (lm/W)、功率 (W)、顯色指數 (CRI), 可根據客戶需求定制
- 此型號標準之功率因數 (PF) > 0.9, 總諧波指數 THD < 15%, 可按客戶需要生產低總諧波指數 < 10%
- 此型號燈管可向實驗室發出之安全燈管測試, 環保物料 (RoHS), 光生物安全為 Exemption Group 及其它測試, 保證客戶使用更安心滿意